

TEXAS DEPARTMENT OF INSURANCE

Engineering Services Program / MC 103-3A 333 Guadalupe Street P.O. Box 149104 Austin, Texas 78714-9104
Phone No. (512) 322-2212 Fax No. (512) 463-6693

PRODUCT EVALUATION

WIN-1591

Effective Date: May 1, 2012

Reevaluation Date: **November 2014**

The following product has been evaluated for compliance with the wind loads specified in the **International Residential Code (IRC)** and the **International Building Code (IBC)**.

This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.

This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code and the Texas Engineering Practice Act.

Clad Wood Ultimate Glider Picture Windows, Non-impact Resistant, manufactured by

Marvin Windows and Doors

P.O. Box 100

Highway 11 West

Warroad, Minnesota 56763-0100

Telephone: (218) 386-4021

General Description:

System	Description	Label Rating	Design Pressure Rating
1	Clad Ultimate Glider Picture Windows; (O)	FW-LC40 71.5 x 71.5; LC-PG40 71.5 x 71.5	± 40 psf

Product Dimensions:

System	Overall Size	Fixed Sash Size
1	71.5" x 71.5"	68.5" x 68.25"

Product Identification (Certification Agency Label on Window):

System		
1	Certification Agency	WDMA
	Manufacturer's Name or Code Name	Marvin Windows and Doors
	Product Name	Clad Ultimate Glider Picture Aluminum-Clad Wood
	Test Standards	AAMA/WDMA 101/I.S.2/A440-05; AAMA/WDMA/CSA 101/I.S.2/A440-08

Impact Resistance:

Impact Resistant	Requirement
No	Impact protective system required when product is installed in areas where windborne debris protection is required

Installation: The wood wall framing members shall be minimum Spruce-Pine-Fir dimension lumber. The windows shall be secured to the wall framing utilizing the nailing fin of the window with minimum 2" long 11 gauge smooth shank roofing nails. The fasteners shall be spaced approximately 8 to 10 inches on center along the perimeter of the window. In addition, the window frame shall be secured to the wall framing with minimum No. 8 x 3" screws. Along the side jambs, the fasteners shall be placed 6 inches from each corner and one (1) at the mid span. Along the head and the sill, one (1) fastener shall be located at the

mid span. The fasteners shall be long enough to penetrate a minimum of $1\frac{1}{2}$ inches into the wall framing.

Note: The manufacturer's installation instructions shall be available on the job site during installation. All fasteners shall be corrosion resistant as specified in the International Residential Code (IRC) and the International Building Code (IBC) and the Texas Revisions.